

Übersicht Gasdruckfedern Standard

Typ	Ø Kolbenstange	Ø Zylinderrohr	Ausschubkraft	Progression
G 02-06	2 mm	6 mm	5-40 N	20 %
‣ G 03-08	3 mm	8 mm	5-100 N	30 %
‣ G 03-10	3 mm	10 mm	5-100 N	20 %
‣ G 04-12	4 mm	12 mm	10-180 N	25 %
‣ G 06-15	6 mm	15 mm	40-400 N	22 %
‣ G 06-19	6 mm	19 mm	40 - 400 N	17 %
‣ G 08-19	8 mm	19 mm	50 - 700 N	30 %
‣ G 08-23	8 mm	23 mm	50 - 700 N	18 %
‣ G 10-23	10 mm	23 mm	100 - 1200 N	30 %
‣ G 10-28	10 mm	28 mm	100 - 1200 N	20 %
‣ G 10-40	10 mm	40 mm	150 - 1200 N	8 %
‣ G 14-28	14 mm	28 mm	150 - 2500 N	40 %
‣ G 14-40	14 mm	40 mm	150 - 2500 N	16 %
‣ G 20-40	20 mm	40 mm	300 - 5000 N	40 %
‣ G 22-40	22 mm	40 mm	500 - 6000 N	43 %
‣ G 25-55	25 mm	55 mm	500 - 7500 N	40 %
‣ G 30-65	30 mm	65 mm	750 - 10000 N	35 %